

AFM SAFECHOICE Carpet Care System

1. Carpet Shampoo

1. **Coverage-** 1:8 ratio with water (1 pint of carpet shampoo to 1 gallon of water) 1 gallon of the carpet shampoo mixture will cover approximately 300 square feet. Use a higher or lower concentration based on your needs.
2. Apply mixture with a garden sprayer or a carpet shampooer.
3. Let soak for 5-10 minutes.
4. Extract with a wet/dry shop vac or a carpet shampooer on an extraction setting.



2. Carpet Seal (*this is the most important and labor intensive step*)

1. **Coverage-** 300 square feet per gallon.
2. While the carpet is still damp, apply the Carpet Seal using the garden sprayer. Do not dilute, Carpet Seal is ready to use.
3. Scrub in the Carpet Seal using a clean, heavy bristle garage broom. We recommend using a heavy, natural bristled broom.
 4. Once the Carpet Seal has been brushed vigorously down the fiber to the plastic backing, wrap the broom head with clean, large towels. Thoroughly scrub the surface of the carpet until the fibers are dry.



(Be advised: If the Carpet Seal is not completely removed from the fibers, a white, salt like film can develop which will make the fiber stiff. This can be removed by starting over and re-shampooing)

3. Carpet Lock Out

1. **Coverage-** 300 square feet per gallon.
2. Once the carpet is completely dry from the first 2 steps, Carpet Lock Out can be applied using the garden sprayer. The Lock Out is ready to use, and does not require dilution.
3. Apply the Lock Out to the surface of the carpet fibers and allow to dry without traffic or disruption.
4. 12-24 hour cure time DEPENDENT on humidity, temperature and air movement. Large fans and air flow are recommended to promote faster cure time.



IMPORTANT: The effectiveness of this system will vary depending on carpet style, application methods, and how closely you follow these instructions. When in doubt, ask for professional recommendations. Expect an 80-95% reduction in toxic outgassing when done properly.



Green Design Center
262-446-6702
1-800-292-4838

Please call us with any questions or concerns you may have regarding application of this product.